

## Tapered roller bearing 6575-6535-TIMKEN - 6575-6535-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/6575-6535-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> e <sub>2</sub>	Static C <sub>3</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
76.200	161.925	53.975	43000	1.40	114000	70100	1.48	52000	6575	6535
3.0000	6.3750	2.1250	58000		25000	12500		118000		

  

Bearing Dimensions											Geometry Factors			Bearing Weight
Width B	Width C	ER Cr	Max Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Backing Shoulder Dia. d <sub>2</sub>	Max Housing Fillet Radius R <sub>2</sub>	Backing Shoulder Dia. D <sub>1</sub>	Backing Shoulder Dia. D <sub>2</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(3)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
50.100	42.802	-13.2	0.4	92.0	104.0	3.3	154.0	161.0	4.1	0.0	198.0	33.0	0.1027	5.40
2.1000	1.6875	-0.52	0.25	3.62	4.09	0.13	6.09	6.36	0.16	0.04				11.20

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952321745
Inside diameter	76.2 mm
Inside diameter	3" inch
Outside diameter	161.925 mm
Outside diameter	6 3/8" inch
Thickness	53.975 mm
Thickness	2 1/8" inch
Weight	5400 g
Packaging	1
Standard	No standard

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE