


## Tapered roller bearing 9380-9321-TIMKEN - 9380-9321-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/9380-9321-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**



Bearing Dimensions			Load Ratings							Part Number	
Bore d	O.D. D	Width B	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Static <sup>(1)</sup> C <sub>0</sub>	Factor <sup>(2)</sup> K	Dynamic <sup>(1)</sup> C <sub>02</sub>	Factor <sup>(2)</sup> K	Static <sup>(1)</sup> C <sub>0</sub>	Inner	Outer
mm	mm	mm	N		N		N		N		
76.200	171.450	49.212	302000	0.25	94100	123000	0.16	301000	30000	0280	0321
3.0000	6.7000	1.9375	81000		21200	27700		79800			

Bearing Dimensions										Geometry Factors			Bearing Weight	
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Cage A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>		G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm				kg	
48.028	31.750	4.3	3.5	98.2	105.0	3.3	166.0	147.8	8.9	3.9	117.9	18.6	0.1003	5.11
1.8725	1.2500	0.17	0.14	3.87	4.13	0.13	6.46	5.79	0.35	0.16				11.26

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952321806
Inside diameter	76.2 mm
Inside diameter	3" inch
Outside diameter	171.45 mm
Outside diameter	6 3/4" inch
Thickness	49.212 mm
Thickness	1 15/16" inch
Weight	5116 g
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE