

## Tapered roller bearing 941-932-TIMKEN - 941-932-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/941-932-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(1)</sup> C <sub>2</sub>	Factor <sup>(2)</sup> K	Static C <sub>2</sub>	Inner	Outer	
mm	mm	mm	N	mm	N	mm	N	mm	mm	
101.600	212.225	66.675	57200	0.33	14800	82700	1.79	70600	941	932
4.0200	8.3750	2.6250	12600		3300	18500		17300		

  

Bearing Dimensions										Geometry Factors		Bearing Weight		
Width B	Width C	ET C <sub>2</sub> μm	Max Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius R <sub>2</sub>	Backing Shoulder Dia. D <sub>1</sub>	Cage A <sub>1</sub> (1)	A <sub>2</sub> (1)	G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>			
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg		
66.675	58.875	-16.8	7.6	117.0	136.8	3.3	163.1	187.0	6.6	1.3	338.6	35.8	0.1153	10.96
2.6250	2.1250	-0.78	0.30	4.61	5.12	0.13	7.80	7.36	0.26	0.05				24.17

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952324265
Inside diameter	101.6 mm
Inside diameter	4" inch
Outside diameter	212.725 mm
Outside diameter	8 3/8" inch
Thickness	66.675 mm
Thickness	2 5/8" inch
Weight	10960 g
Packaging	1
Standard	No standard

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE