

Tapered roller bearing 941-932-TIMKEN - 941-932-TIMKEN

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/941-932-timken>

TAPERED ROLLER BEARINGS											
SINGLE-ROW • TYPE TS											
TYPE TS											
Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic ⁽¹⁾ C_1	Factor ⁽²⁾ e	Dynamic ⁽³⁾ C_{10}	Factor ⁽⁴⁾ K	Static C_0	Inner	Outer		
mm	mm	mm	N		N		N				
in	in	in									
101.600	212.725	66.675	57900	0.04	148000	82700	1.78	786000	941	932	
4.0000	8.3750	2.6250	12600		33000	18800		173000			
Bearing Dimensions											
Shaft			Housing			Cage			Geometry Factors		
Width B	Width C	ER. Dr. μm	Max Shaft Fillet Radius R_{fs}	Backing Shoulder Dia. d_s	Max Housing Fillet Radius r_{fs}	Backing Shoulder Dia. D_s	A_{10}	A_{11}	G_1	G_2	C_1
mm	mm	mm	mm	mm	mm	mm	mm	mm			kg
in	in	in	in	in	in	in	in	in			lb
66.675	53.975	-15.8	7.6	117.0	136.6	3.3	193.1	187.0	6.6	1.3	358.6
2.6250	2.1250	-0.78	0.28	4.61	5.12	0.13	7.63	7.38	0.26	0.05	19.96

PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952324265
Inside diameter	101.6 mm
Inside diameter	4" inch
Outside diameter	212.725 mm
Outside diameter	8 3/8" inch
Thickness	66.675 mm
Thickness	2 5/8" inch
Weight	10960 g
Packaging	1
Standard	No standard

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE