


Tapered roller bearing 32312-JR-JTEKT - 32312-JR-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32312-jr-koyo>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
60	130	48.5	46	37	3	244	315		3 100	4 200	32312JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	r _{2a} min.	r _{2a} max.		Y ₁	Y ₀	
2FD	32.3	74	74	118	107	120	4	11.5	2.5	2	0.35	1.74	0.96	2.99	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952408903
Inside diameter	60 mm
Inside diameter	2.362" inch
Outside diameter	130 mm
Outside diameter	5.118" inch
Thickness	48.5 mm
Thickness	1.909" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE