


Tapered roller bearing 32312-JR-JTEKT - 32312-JR-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/32312-jr-koyo>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C_r	C_{0r}	Grease lub.	Oil lub.						
60	130	48.5	46	37	244	315	3 100	4 200			32312JR			
Dimension series to ISO 3055 (Refer. J)	Load center a	Mounting dimensions (mm)								Constant e	Axial load factors		Mass (kg)	
		d_a min.	d_b max.	D_a max.	D_b min.	S_a min.	S_b min.	r_a max.	r_b max.		Y_1	Y_0		
2FD	32.3	74	74	118	107	120	4	11.5	2.5	2	0.35	1.74	0.96	2.99

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952408903
Inside diameter	60 mm
Inside diameter	2.362" inch
Outside diameter	130 mm
Outside diameter	5.118" inch
Thickness	48.5 mm
Thickness	1.909" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE