


## Tapered roller bearing 30317-DJR-JTEKT - 30317-DJR-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/30317-djr-koyo>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
85	180	44.5	41	28	253	317	1 900	2 600			30317DJR			
Dimension series to ISO 3055 (Refer. J)	Load center a	Mounting dimensions (mm)						Constant e	Axial load factors		Refer. Mass (kg)			
		d <sub>a</sub> min.	d <sub>b</sub> max.	D <sub>a</sub> max.	D <sub>b</sub> min.	S <sub>a</sub> min.	S <sub>b</sub> min.		r <sub>a</sub> min.	r <sub>b</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
7GB	56.3	103	103	166	143	169	6	16.5	3	2.5	0.83	0.73	0.40	4.81

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122279
Inside diameter	85 mm
Inside diameter	3.346" inch
Outside diameter	180 mm
Outside diameter	7.087" inch
Thickness	44.5 mm
Thickness	1.752" inch
Weight	500 g
Packaging	1
Standard	No standard

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE