

Tapered roller bearing 65237A-65500-JTEKT - 65237A-65500-KOYO

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/65237a-65500-koyo>

Single-row tapered roller bearings
inch series

Koyo

101cn series

Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{1 max.}	<i>r</i> _{2 max.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
60.325	127.000	44.450	44.450	34.925	1.6	3.2	208	269	3 300	4 400

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factor		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _s	<i>d</i> _b	<i>D</i> _s	<i>D</i> _b	<i>r</i> _{s max.}	<i>r</i> _{b max.}		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
65237A	65500	35.2	78.0	71.0	107.0	119.0	1.6	3.2	0.49	1.23	0.68	1.59	1.02

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952428413
Inside diameter	60.325 mm
Inside diameter	2 3/8" inch
Outside diameter	127 mm
Outside diameter	5" inch
Thickness	44.45 mm
Thickness	1 3/4" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE