

Deep groove ball bearing single row 3020-SC-NICE - 3020-SC-NICE

<https://www.123bearing.eu/bearing-housing/deep-groove-bearing/single-row/3020-sc-nice>

3000 Series® Semi-Ground Radial Bearings (con't)

NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT RING
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3020™		SC				+0.005 +0.13 -0.000 -0.00	+0.000 +0.50 -0.0005 -0.013
						0.4375 11.113	1.3750 34.925

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.4375 11.113	940 4183	850 3783	0.12 0.05	0.658 16.71	1.203 30.58	0.025 0.64

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3020 and larger +0.0001/-0.0006 (+/-0.0001/-0.015)

PRODUCT FEATURES

Brand	NICE
N° Ean13	3663952558462
Inside diameter	11.113 mm
Inside diameter	7/16" inch
Outside diameter	34.925 mm
Outside diameter	1 3/8" inch
Thickness	11.113 mm
Thickness	7/16" inch
Weight	50 g
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE