

## Drawn cup roller bearing BA2420-Z-IKO - BA2420-Z-IKO

<https://www.123bearing.eu/bearing-housing/needle-roller-bearing/drawn-cup/ba2420-z-iko>



Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed(I)	Assembled inner ring		
$F_w$	$D$	$C$	$d$	$h_0$	$H$	$T$	$C$	$C_0$	rpm			
			Min.	Max.	Min.	Max.	Min.	Max.				
38.100	1.1247	47.625	1.6 & B	31.761	1.290	2.4			9000	74200	9000	RB 2420

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060601476
Inside diameter	38.1 mm
Inside diameter	1 1/2" inch
Outside diameter	47.625 mm
Outside diameter	1 7/8" inch
Thickness	31.75 mm
Thickness	1 1/4" inch
Limiting speed	9000 rpm
Dynamic load	39 kN
Static load	74.2 kN
Packaging	1

[contact@123bearing.eu](mailto:contact@123bearing.eu)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE