


Tapered roller bearing LM522548-LM522510-JTEKT - LM522548-LM522510-JTEKT

<https://www.123bearing.eu/bearing-housing/roller-bearing/tapered/lm522548-lm522510-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_{max}	r_{min}	C_r	C_{10}	Grease lub.	Oil lub.
109.987	159.987	34.925	34.925	29.985	7.9	3.2	184	319	2 200	2 900

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d_s	d_b	D_s	D_b	$r_{s \text{ max}}$	$r_{b \text{ max}}$	e	Y_1	Y_2	Inner ring	Outer ring
LM522548	LM522510	32.9	131.0	121.0	146.0	153.0	7.9	3.2	0.40	1.50	0.82	1.52	0.784

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952430157
Inside diameter	109.987 mm
Inside diameter	4.33" inch
Outside diameter	159.987 mm
Outside diameter	6.299" inch
Thickness	34.925 mm
Thickness	1 3/8" inch
Packaging	1

contact@123bearing.eu

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE